

AC-DC 20W





6A-201DAXX

Features:

- Universal AC Input 90~264Vac
- Low ripple noise
- No minimum load requirement
- 100% burn in test
- 1 year warranty
- L=1200±100mm
- Meet EPS 2.0 LEVEL VI
- Safety: UL/CUL, CB, GS, CE, FCC



Dimension:



Model No.	Output		Additional Safety
	V	A	
6A-201DA05	5V	4A	CCC, BSMI
6A-201DA06	5.95V	3A	

Specification:

Input	Voltage	AC 90V~264V Universal full range
	Frequency	47-63Hz
	Current	500mA
	Leakage Current	< 0.25mA
Others	Start up time	< 3000mS @115VAC Full Load
	Rise time	<100mS
	Hold up time	>20mS @ 230Vac/50Hz input
	Cooling	Natural Cooling
Environment	Temperature	Operating: 0~40; Storage: -10~+70
	Humidity	Operating: 20%~85%; Storage: 10%~95%(Non Condensing)
M. T. B. F	50k Hours	
Safety	UL 60950-1, CSA C22.2 No. 60950-1, EN60950-1, IEC 60950-1	
EMC	EMI	FCC CFR 47 PART 15 , EN55022 , EN61000-3
	EMS	EN55024 (EN61204-3) EN61000-4



ISO 14001



For reference only